



MKF 6 µm - G 1/8" -400 gr +
500 gr SKT-PZ-MU

Item number: DIA52114821
EAN: 4103810700750

Technical data

Connection discharge side: G 1/8"
Diameter of grease piston (mm): 10
Max. delivery pressure (bar): 400
Burst pressure system (bar): 850
Burst pressure grease gun head (bar): 1200
Delivery rate stroke (cm³): 2,2
Filling: 500 g screw-in cartridge (12 524), 400 g screw-in cartridge
Lacquering hand levers: moss green, RAL 6005
Colour handgrips: marker green, RAL 1107077
Dimensions LxWxH (mm): 380 x 185 x 30
Weight (kg): 1,08

Specification

- With hose bracket
- High pressure hose, G 1/8" male, 11 x 300 mm, with sealing ring (12 755 828)
- Precision machined coupler, 4 claws, G 1/8" female (12 743)
- Centering ring adapter (88 683 101)
- Grease gun head, zinc die casting Z 410
- Ball seat valve, galvanized (85 627)

Special notes

- Supports grease from penetration grade according to ASTM-mill penetration (10⁻¹ mm): NLGI 3 till 10°C
- Ergonomic contoured safety handgrip
- Extended product lifetime based on an optimal combination of zinc (grease gun head) and polished steel (reciprocating)
- Unmatched surface Ra (0,4 µm) and tolerance (6 µm) of the piston tube for the main piston - no dummy apparent lubrication
- Optimal leverage for operating the hand lever, thus the force required for lubrication is as low as possible
- All screw connections are sealed
- Quick exchange of cartridges
- Environmental friendly, cartridge can be emptied completely
- Filling level and type of grease visible

Packaging

Dimensions LxWxH (mm): 381 x 192 x 67
Weight including package (kg): 1,2
Pallet Quantity (h = 1,2 m): 168 pcs.
Packing unit: 1,0