

WASTE OIL EQUIPMENT ACCESSORIES

SPECIALTY DRAINERS



WASTE OIL SUCTION ACCESSORIES



372 003

372 003 Transparent chamber kit

10 l transparent chamber, mounts on 70 and 100 litres waste oil suction units. Complete with vacuum pump, vacuum gauge and 2 m suction hose with rubber grip and connector for Mercedes Benz vehicles.

737 967 Suction hose kit

2 m transparent suction hose with rubber grip, shut-off valve and connector for Mercedes Benz vehicles.

WASTE OIL COLLECTION BOWLS



372 002

372 002 Collection bowl for 100 litres waste oil receivers

Includes 20 l metal bowl, oversized extension and anti-splash grid, tube, shut-off valve, swivel and adapter for fixing the tube to receivers.



743 305

373 002 Collection bowl for 100 litres waste oil receivers

Includes 20 l metal bowl, tube, shut-off valve, swivel and adapter for fixing the tube to receivers.

743 305, 20 litres collection bowl

20 l metal bowl with tube and 2" bung adaptor for fixing to an empty drum.

DRUM TROLLEYS



431 000



432 000

432 000, 185 kg / 200 litres drum trolley

431 000, 50 kg drum trolley

USED FLUID COLLECTION UNITS - SPECIALTY DRAINERS

436 100



Low level mobile drainers for gravity collection of waste oil and used antifreeze solutions. Recommended to use when a hoist or a service pit is not available. Gravity discharge using an evacuation pump kit (PN 559 100) through a dry break hydraulic connector (PN 950 352, not included).

435 000 Low level mobile drainer, 20 litres
20 litres (5.2 US gallons)

436 000 Low level mobile drainer, 95 litres
95 litres (25 US gallons)

436 100 Anti-freeze recovery unit

Low level drainer 436 000 equipped with a DF50 diaphragm pump. Thanks to the diaphragm pump and the delivery gun is possible to reuse the antifreeze.

437 300



437 300 Motor Bike waste oil drainer, 35 litres

Unit with low profile pivoting bowl for gravity collection from motorbikes on service lifts. Air pressure discharge. The discharge hose also serves as level gauge. Includes a safety valve and an air pressure regulator, factory set to guarantee a low pressure and safe discharge of the unit. Maximum/minimum height of the top edge of the bowl: 1.000 / 700 m.

439 100



439 100 Pit rolling drainer, 95 Litres

Rolling drainer for being installed between pit rails with minimum / maximum width of 1.040 / 1.450 mm. 95 litres (25 US gallons) capacity. Unit includes antispash grid, four vertical and four horizontal rollers for easy rolling and an 1-1/4" outlet with ball valve. The unit allows the connection of a hydraulic connector for discharging with a discharge pump kit.