

## DIESEL METERS

Nutating-disk meter for diesel with mechanical register. Very low pressure drop; it can be used for gravity fed applications. Resettable partial reading up to 999,9 liters and permanent 6 digit totaliser. 1" BSP (F) inlet and outlet, both with flange for optional flange mounting. The meter allows to orientate the inlet and outlet in four different positions. Maximum working pressure: 10 bar. Flow range: 20 to 100 l/minute. Precision after calibration: ± 1%. Meter valid for non commercial applications only.

- 680 300 Diesel meter with mechanical 3 digit register**
- 680 301 Diesel meter with mechanical 4 digit register**
- 689 044 Swivel elbow for meter outlet 1" BSP (MF)**



680 301



361 000



688 100

689 090

## DIESEL NOZZLES

- 361 000 Aluminium manual nozzle. Fluid inlet: 1" BSP (F) - 100 l/min.**
- 689 910 Thermoplastic manual nozzle. Fluid inlet: 1" BSP (F) - 80 l/min.**

- 688 300 Aluminium automatic nozzle. Fluid inlet: 1" BSP (F) - 60 l/min.**
- 688 001 Aluminium automatic nozzle. Fluid inlet: 1" BSP (F) - 80 l/min.**
- 688 100 Aluminium automatic nozzle. Fluid inlet: 1" BSP (F) - 120 l/min.**
- 364 030 Aluminium inlet swivel. 1" BSP (MF) (included in automatic nozzles).**

## DIESEL FILTERS

When fitted at the pump outlet they eliminate dirt up to 30 microns and the water contained in the diesel.

- 689 090, 65 l/min diesel filter, 1" BSP (F).**
- 689 098, 110 l/min diesel filter, 1" BSP (F).**

- 689 091 Replacement cartridge**  
For filter 689 090.
- 689 099 Replacement cartridge**  
For filter 689 098.

## HOSES FOR DIESEL

Rubber hose with metal swagged 1" BSP (M) fittings.

689 021



PART No.	HOSE LENGTH AND Ø
<b>689 021</b>	4 m x Ø 19 mm
<b>689 022</b>	4 m x Ø 25 mm
<b>689 023</b>	6 m x Ø 19 mm

## PUMP BRACKETS

- 689 052 Pump wall bracket**
- 756 200 Bracket with handle**
- 360 137 Universal bracket for 205 litres drum and IBCs**

756 200




## SUCTION TUBES

Telescopic suction tubes for connecting directly to the pump inlet. 1" BSP (M) connection, 2" (M) bung adaptor and foot valve with filter, (PN 689 042).

- 689 035 For drums or tanks with a maximum height of 1m**
- 689 036 For tanks with a maximum height between 1 and 1,75 m**
- 689 037 Suction assembly. Includes 2 m x Ø 25 mm hose, shut off valve and telescopic suction tube 689 036**

689 035



689 036

## CONNECTION ADAPTORS FOR HOSES

- 689 042 Foot valve with filter for suction tube, 1" BSP (F)**
- 689 015 Brass foot valve with filter for suction tube, 1" BSP (F)**

- 689 041 Suction filter for hose, Ø 25 mm**
- 689 016 Brass suction filter for hose, 1" BSP (F)**

- 689 040 «Y» strainer, 1" BSP (F)**
- 689 019 Brass «Y» strainer, 1" BSP (F)**

- 689 047 Hose barb adaptor Ø 19 mm with clamps, 1" BSP (M)**
- 689 048 Hose barb adaptor Ø 25 mm with clamps, 1" BSP (M)**

- 689 017 Brass hose barb adaptor Ø 19 mm with clamps, 1" BSP (M)**
- 689 018 Brass hose barb adaptor Ø 25 mm with clamps, 1" BSP (M)**

- 689 053 Pump, drum and suction kit connection adaptor, 2 x 1" BSP (M) / 2" BSP (M)**



689 041



689 042



689 040



689 053



689 047

## SUCTION HOSES

Transparent PVC spring reinforced hoses. Suction hoses include swagged metal 1" BSP (M) fittings and foot valve.

- 689 030, 2 m x Ø 25 mm**
- 689 031, 4 m x Ø 25mm**

689 030

