

PUMPMASTER 35 - 60 : 1 RATIO GREASE PUMPS

486 210 - 423 021

PUMPMASTER 35 - 60:1 RATIO PACKAGES FOR 20 & 18 KG PAILS



	MOBILE PACKAGE FOR 20 KG PAILS (2)	PORTABLE PACKAGE FOR 18 KG PAILS
PART No.	486 210	423 021
PUMP	530 630	530 630
DRUM COVER	-	418 013
FOLLOWER PLATE	-	417 001
HOSE CONNECTION KIT	-	-
GREASE GUN WITH Z-SWIVEL	413 080	413 080
DELIVERY HOSE	2 m x 3/8" 412 390	2 m x 3/8" 412 390
DRUM TROLLEY	480 021(2)	-

- (1) Shielded unit. Includes base with 2 wheels and 2 castors.
- (2) Shielded unit. Includes base with 4 castors.

424 062



MOBILE EXTRUSION UNIT FOR 12-20 KG PAILS

Mobile unit specially designed for its use with hard to pump sticky and high viscosity greases (up to NLGI3). The pump's lower end is fixed to an inductor plate and the pump is mounted to a pneumatic piston that elevates the pump for replacing an empty pail. The pneumatic piston also acts when the pump is in use, pushing the inductor plate against the grease, aiding the pump prime, making possible to pump very high viscosity grease.

The unit includes a PM35 - 60:1 pressure ratio pump and it is mounted to a rolling base with 4 wheels, two of them with brake.

424 062 Mobile extrusion unit

Includes 3 m high pressure hose and a grease control gun with Z-swivel and hydraulic nozzle. **424 063 Mobile extrusion unit**

Same as model 424 062 but with no outlet hose and grease control gun.

Not included options:

239 001: 1/4" BSP (M) - 3/8" BSP (M) connection adaptor. **240 500:** Air filter and pressure regulator, 1/4" BSP (FF).

360 111: Hose reel pivoting bracket.360 127: Control gun holder and drip tray.

417 001: Follower plate 298 - 260 mm. For 12,5 kg and 18 Kg pails.

417 002: Follower plate 370 - 330 mm. For 50 kg standard diameter drums.

417 003: Follower plate 405 - 360 mm. For 50 kg large diameter drums.

417 005: Follower pate 340 - 300 mm. For 20 Kg pail.

411 100: In line grease meter for grease control gun.