

# PUMPMASTER 45 & 60 GREASE PUMP ACCESSORIES

## AIR ACCESSORIES FOR GREASE PUMPS

### HEAVY DUTY DRUM COVERS



418 026



418 017

Covers are made from heavy steel gauge to withstand hard usage. Cover flange provides rigidity and maintains solid position on drum. Grease pump mounts in centre of cover with four screws.

PART No.	APPLICATION	MAX. - MIN. DRUM DIAMETER
FOR PM45 & 60 PUMPS		
<b>418 026</b>	185 kg - 400 lb	620 - 580 mm
<b>418 017</b>	50 kg - 120 lb	395 - 350 mm

### HEAVY DUTY FOLLOWER PLATES



417 009




417 010

Follower plates eliminate channeling and air pockets, keep lubricant free from contaminants, remove all grease from the drum and aid pump prime. HD follower plates are manufactured in galvanized steel and has a central part in aluminum that adjusts to the pump tube using O'ring to create a perfect seal.

PART No.	APPLICATION	MAX. - MIN. DRUM Ø
FOR PM45 & 60 PUMPS		
<b>417 009</b>	185 Kg - 400 lb. drums	590 - 550 mm
<b>417 010</b>	50 Kg - 120 lb. drums	305 - 360 mm
<b>417 011</b>	50 Kg - 120 lb. drums	370 - 330 mm

### HOLD DOWN KITS



741 604

*Pump, follower plate, drum cover and drum are not included.*

Allow to fix a 185 kg or a 50 kg drum to a lube truck bed when used together with drum covers 418 026 and 418 017.

**741 604 Hold down kit for 185 kg - 400 lb drums**

For use with drum cover 418 026.

**741 605 Hold down kit for 50 kg - 129 lb drums**

For use with drum cover 418 017.

### AIR ACCESSORIES

PART No.	THREAD	COMPONENT	APPLICATION
<b>AIR TREATMENT UNITS</b>			
<b>241 001</b>	1/2" BSP (FF) with 1/2" BSP(M) - 3/8" BSP(F) adaptors	Combined air filter, regulator and lubricator	<b>PM35 pumps</b>
<b>241 501</b>		Combined air filter and regulator	
<b>241 201</b>		Air line regulator	
<b>242 102</b>	3/4" BSP (FF)	Combined air filter, regulator and lubricator	<b>PM45 and PM60 pumps</b>
<b>242 302</b>		Air filter	
<b>242 202</b>		Air line regulator	

PART No.	THREAD	APPLICATION
<b>STANDARD SERIES QUICK COUPLERS</b>		
<b>253 138</b>	3/8" BSP(F)	<b>PM35 pumps</b>
<b>253 112</b>	1/2" BSP (F)	<b>PM45 and PM60 pumps</b>
<b>SAFETY QUICK COUPLERS</b>		
<b>250 638</b>	3/8" BSP(F)	<b>PM35 pumps</b>
<b>250 612</b>	1/2" BSP (F)	<b>PM45 and PM60 pumps</b>

PART No.	THREAD	APPLICATION
<b>AIR NIPPLES</b>		
<b>259 038</b>	3/8" BSP(M)	<b>PM35 pumps</b>
<b>259 012</b>	1/2" BSP (M)	<b>PM45 and PM60 pumps</b>



240 000

253 112



250 612



259 012



### AIR AND GREASE CONNECTION KITS



534 103

**534 103** Includes 1 m x 3/8" air hose (PN 247 710) with 3/8" - 1/2" BSP (MM) connection threads, quick air coupler 251 438, air nipple 255 338, 1,5 m x 3/8" high pressure grease hose (412 392) with 3/8"-1/2" BSP (MM) connection threads. **For use with all PM45 and PM60 grease pumps except with pump PM60 12:1 ratio grease pump.**

### CAM-LOCK ADAPTORS



753 110



950 358

Allow to fix a pump horizontally or vertically to grease bags, totes and other type of containers.

**753 110 Male Cam-Lock adaptor**

Fixes to the bottom end of the grease pump body. Fits any standard 3" female Cam-Lock connector.

**950 358 Female Cam-Lock connector**

Connection thread 3" BSP (F).