

## TECHNICAL SPECIFICATIONS

Li-Ion Battery voltage	20 V
Li-Ion Battery capacity	2,0 Ah / 4,0 Ah
90 min battery charger	240 - 220 V / 50 - 60 Hz and 120 V 60 Hz
Maximum pressure	700 bar (10,000 psi)
Safety valve set pressure	500 bar (7,250 psi)
Flow rate - high	160 g/min (5.7 oz/min)
Flow rate - low	100 g/min (3.6 oz/min)
Grease cartridges per battery charge <sup>(1)</sup>	24 (2 Ah battery) - 40 (4 Ah battery)
Display functions	Battery level gauge, grease meter, grease level gauge, stall alarm, loss of prime alarm.
Measuring units	Grams, ounces
LED flashlight	Yes, with on/off function
Hose length	1.100 mm (44")
Shoulder strap	Included
Grease gun weight	3,2 kg (7 lb)
Manual	816 809

<sup>(1)</sup> Low speed, low flow mode at free delivery

## MODELS

<b>160 500</b>	Battery grease gun with 1 x 2 Ah battery pack. 240 - 220 V / 50 - 60 Hz
<b>160 501</b>	Battery grease gun with 2 x 2 Ah battery pack. 240 - 220 V / 50 - 60 Hz
<b>160 510</b>	Battery grease gun with 1 x 4 Ah battery pack. 240 - 220 V / 50 - 60 Hz



## Accessories

<b>169 503</b>	Carrying case
<b>169 012</b>	Grease outlet hose
<b>169 500</b>	Battery charger
<b>169 020</b>	2 Ah - 20 V Lithium-Ion battery pack
<b>169 021</b>	4 Ah - 20 V Lithium-Ion battery pack
<b>710 310</b>	Tube kit for 160 500
<b>710 026</b>	Tube kit for 160 510
<b>169 014</b>	Metallic adapter for screw cartridges TR20-TR57
<b>169 015</b>	Metallic adapter for screw cartridges 1"BSP-TR57