



## Brackets

	<b>360 102</b> Wall bracket
	<b>360 120</b> Floor bracket

**Bung adaptors 2" (M)** connection for drum and tanks bung openings

	<b>Bung adaptor for PM2</b>
<b>360 000</b>	Bung adaptor for PM2 3:1 pumps. Pump tube outside diameter: 34 mm.
<b>360 001</b>	Bung adaptor for PM2 1:1 pumps. Pump tube outside diameter: 52 mm.

## Hose connection kit



### PM2 pump connection kit

<b>362 910</b>	1 m x 1/4" air hose 246 010, one 1/2" BSP (M) x 1/4" BSP (F) connection adapter 945 516, 1 m x 1/2" oil hose with 1/2" BSP (MM) fittings, one automatic quick air coupling 1/4" BSP (F) 253 114 and one quick air connector 1/4" BSP (M).
----------------	---

**Suction Assemblies and suction hoses** Suction assemblies for wall mounted stub pumps. Assemblies include Ø 42 suction tube with foot valve, height adjustable 2" bung adaptor and 2 m x 3/4" rubber connection hose.



<b>367 000</b>	Suction assembly for 1.000 l IBC and 205 l drums. 1.060 mm suction tube.
<b>367 003</b>	Suction assembly for tanks. 1.600 mm suction tube.
<b>367 011</b>	Spring reinforced transparent suction hose. For 205 l drums and 1.000 l IBC. 3 m x 3/4" .
<b>367 012</b>	Spring reinforced transparent suction hose with foot valve. For 205 l drums and 1.000 l IBC. 3 m x 3/4" , includes foot valve.
<b>367 102</b>	Pump suction kit. Includes suction assemble 367 000 and pump bracket 360 102.

## Adjustable safety relief valves



Adjustable safety relief valves for pneumatic pumps to limit the overpressure in the fluid line, generated, for instance, by the thermal expansion of the fluid confined in the piping. Made out of zinc-plated steel, they are regulated by means of an Allen screw located on the side of the valve.

<b>609 013</b>	Adjustable safety relief valve. 20 - 30 bar (290 - 435 psi). 1/4" BSP (M) - M10 x 1.25.
<b>609 014</b>	Adjustable safety relief valve. 10 - 20 bar (145 - 290 psi). 1/4" BSP (M) - M10 x 1.25.
<b>609 015</b>	Adjustable safety relief valve. 30 - 50 bar (435 - 725 psi). 1/4" BSP (M) - M10 x 1.25.

## Pressure relief valve SAMOA pumps

Include a 1/4" plug that can be removed and replaced with a pressure relief valve.



<b>609 007</b>	Opens at approx. 60 bar. Possibility to connect either a 1/4" hose with a clamp or a hose with 1/8" BSP (F) fitting as oil return live.
----------------	---

## Autostop valve, 1/2" BSP (F)



<b>609 016</b>	Shuts off air to the pump when lubricant drum/tank is empty or when the line is broken.
----------------	---