SAMOA

360 120

360 108

360 132

OIL PUMP ACCESSORIES

PUMP BRACKETS

PM2 AND PM4 PUMP BRACKETS

360 102 Wall bracket

360 120 Floor bracket

360 106 Bracket for fixing a pump and a hose reel on top of a 1.000 l IBC
Requires pump bracket 360 102 (not included).
360 107 Bracket for fixing a pump and a hose reel laterally on a 1.000 l IBC

Requires pump bracket 360 102 (not included). **360 108 Bracket for fixing a pump laterally on a 1.000 l IBC** Requires pump bracket 360 102 (not included).

PM35 PUMP BRACKETS

360 139 Wall bracket, bung mount pump (2" F). **360 140 Wall bracket**, flange mount pump (4 x M8).

PM45 AND PM60 PUMP BRACKETS 360 132 Wall bracket 360 121 Floor bracket

CONNECTION ADAPTERS AND VALVES

CONNECTION ADAPTERS

945 590, 1/4" BSP (MM).
945 592, 3/8" BSP (MM).
945 558, 1/2" BSP (MM).
945 551, 3/4" BSP (MM).
945 555, 1" BSP (MM).
945 724, 1 1/2" BSP (MM).

945 681, 1 1/2" BSP (M) - 1" BSP (M). **945 552** 1" BSP (M) - 3/4" BSP (M). **945 554,** 3/4" BSP (M) - 1/2" BSP (M). **945 557,** 1/2" BSP (M) - 3/8" BSP (M). **945 567,** 2" BSP (M) - 1 1/2" BSP (M).

565, 2" BSP (M) - 1" BSP (F). **513**, 1 1/4" BSP (M) - 3/4" BSP (F). **670**, 1" BSP (M) - 3/4" BSP (F). **900**, 3/4" BSP (M) - 1/2" BSP (F). **556**, 1/2" BSP (M) - 3/8" BSP (F).

369 601, 1/2" BSP (MM) 45° elbow. **945 572**, 3/4" BSP (MF) 90° elbow. **945 548**, 1/2" BSP (MM) 90° elbow. **945 738**, 3/4" BSP (M) - 3/4" BSP (F) elbow.

LOW AND MEDIUM PRESSURE VALVES

305, 1/4" BSP (FF), 65 bar quarter turn valve. **320**, 3/8" BSP (FF), 65 bar quarter turn valve. **300**, 1/2" BSP (FF), 65 bar quarter turn valve. **303**, 3/4" BSP (FF), 40 bar quarter turn valve. **306**, 1" BSP (FF), 40 bar quarter turn valve. **312**, 1-1/2" BSP (FF), 25 bar quarter turn valve. **308**, 2" BSP (FF), 25 bar quarter turn valve.

HIGH PRESSURE VALVES

950 304, 1/2" BSP (FF), 500 bar quarter turn valve. **950 328**, 3/4" BSP (FF), 400 bar quarter turn valve. **950 329**, 1" BSP (FF), 350 bar quarter turn valve.

AIR LINE SHUTOFF VALVES

950 302, Needle air valve 1/4" BSP (FF). **950 321**, Air valve 1/4" BSP (FF). **950 318**, Air valve 3/8" BSP (FF). **950 319**, Air valve 1/2" BSP (FF).

362 104

950 302

OIL HOSES

Manufactured in NBR with a steel reinforcement braid. With two swaged nuts and male-male adaptors on both ends.

362 100, 1 m x 1/2". Working pressure: 160 bar. Connection threads: 1/2" BSP (MM).
362 101, 1,5 m x 1/2". Working pressure: 160 bar. Connection threads: 1/2" BSP (MM).
362 102, 2 m x 1/2". Working pressure: 160 bar. Connection threads: 1/2" BSP (MM).
362 103, 3 m x 1/2". Working pressure: 160 bar. Connection threads: 1/2" BSP (MM).
362 104, 4 m x 1/2". Working pressure: 160 bar. Connection threads: 1/2" BSP (MM).

362 300, 1 m x 3/4". Working pressure: 100 bar. Connection threads: 3/4" BSP (MM). **362 301**, 1,5 m x 3/4". Working pressure: 100 bar. Connection threads: 3/4" BSP (MM). **362 302**, 1,8 m x 3/4". Working pressure: 100 bar. Connection threads: 3/4" BSP (MM). **362 303**, 3 m x 3/4". Working pressure: 100 bar. Connection threads: 3/4" BSP (MM).



360 102

360 139

945 557

950 306

950 304

a