

## Professional manual filler pumps for centralized lubrication

- › suitable for all greases up to consistency class NLGI 2 (also soft greases)
- › for all commercial grease kegs

### Professional manual filler pumps "Serie FGZ plus" 40673 / 40445



### Filler pump FGZ Combi plus 08761



#### Without trolley

- 40653 FGZ plus 5
- 40784 FGZ plus 10
- 40400 FGZ plus 12.5
- 40671 FGZ plus 15/18
- 40673 FGZ plus 20
- 40675 FGZ plus 25
- 40683 FGZ plus 50
- 40551 FGZ plus 200

#### With trolley

- 40444 FGZ plus 10 mobile
- 40445 FGZ plus 15/18 mobile
- 40446 FGZ plus 20 mobile
- 40447 FGZ plus 25 mobile
- 40448 FGZ plus 50 mobile
- 41403 FGZ plus 15/18 mobile with special follower plate (foam ring)

#### Characteristics

- › works also at temperatures as low as  $-20^{\circ}\text{C}$
- › extremely high suction capacity due to an especially adjusted lift of stroke and increased suction and valve openings
- › robust and wear resisting by reinforced steel lever
- › only low operating force (11 – 16 kp) required
- › follower plate, dust cover, 2 m polyamide grease hose nom. diam. 16, nylon reinforced, self-closing quick coupler 3/8" BSP = G 3/8"
- › output approx.  $30\text{ cm}^3/\text{stroke}$  (1 oz)
- › suction tube diam. 40 mm

#### Without trolley

- 40662 FGZ Combi plus 15/18
- 08761 FGZ Combi plus 25
- 08765 FGZ Combi plus 50

#### With trolley

- 40449 FGZ Combi plus 25 mobile
- 40450 FGZ Combi plus 50 mobile

#### Characteristics

- › see description for FGZ plus
- › for centralized lubrication systems and centralized lubrication systems
- › follower plate, dust cover and combi connector with ball valve, 2 m polyamide grease hose nom. diam. 16, nylon reinforced, self-closing quick coupler 3/8" BSP = G 3/8"