



KITS



PUMPS



METERS



METERED NOZZLES



NOZZLES



WASTE OIL EQUIPMENTS

# OIL HOSE REEL

## FEATURES

- HEAVY DUTY SPRING
- HAND PROTECTION (ON REQ.)
- LONG LASTING
- STEEL HUB

The PIUSI OIL HOSE REEL is an automatic open hose reel for oil, entirely Made in Italy, which includes a built-in heavy duty spring. It can be installed on a wall or inside a closed cabinet and it is suitable for any kind of oil.

### PERFORMANCE

MAX <b>60 BAR</b>	MAX BOUND <b>20M</b>
OPERATING PRESSURE	HOSE LENGTH



**OPEN OIL HOSE REEL HEAVY DUTY**  
(hand protection on request)

**OPEN OIL HOSE REEL**



### PACKAGING

CODE	WEIGHT		PACKAGING			N. BOXES/ EUROPALLET	
	KG	LBS	MM	PCS/PALLET	PCS/BOX		
<b>WITHOUT HOSE</b>							
HN60151200A	14	30,8	550X200X540		1	12	20
HN60153800A	14	30,8	550X200X540		1	12	20
HN60201200A	14	30,8	550X260X540		1	12	20
<b>WITH HOSE</b>							
HA6010120B	16	35,2	550X200X540		1	12	20
HA6015120B	19	41,9	550X200X540		1	12	20
HA6020120B	25	55	550X260X540		1	12	20
HA60153400A	27	60	550X260X540		1	12	20
HA60101000A	25	55	550X260X540		1	12	20
HA60203400A	45	99	640X250X640		1	12	20



FILTRATION



FLUID MONITORING



TANK MONITORING



HOSE REELS



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL






WATER



WINDSCREEN



### INSTALLATION

Different ways to install PIUSI's hose reels: they can be easily placed wherever you need them without any problem about functionality and safety. PIUSI's products are without a doubt designed to support your work in any condition.





### DIMENSIONS

MODEL	OPEN HOSE REEL BIG	OPEN HOSE REEL SMALL
A	495	475
B	460	460
C	152	102
D	200	150
E	246	196
F	150	150
G	200	150
H	12	12



OPEN OIL HOSE REEL HEAVY DUTY



Measures expressed in millimeters

### IN THE BOX

- OIL HOSE REEL
- WALL MOUNT BRACKET
- INSTRUCTION MANUAL

### DETAILS



AUTOMATIC HOSE REELS



4 ROLLS HOSE GUIDE



DIFFERENT INSTALLATIONS



PROTECTION ON REQUEST

### MATERIALS

- BODY: CAST IRON
- HUB: SYNTHETIC STEEL
- TUBE: RUBBER

### TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	HOSE	MAX WORKING PRESSURE	PRESSURE DROP	INLET WITH SWIVEL	OUTLET HOSETAIL	HOSE MAX LENGHT BOUND	HOSE LENGHT
			BSP	BAR	BAR	BSP	BSP	M	M
<b>WITHOUT HOSE</b>									
HN60151200A	REEL OPEN 60B W/O .” MAX 15M OIL (\$)		1/2”	60	-	1/2” MALE	1/2” MALE	15	-
HN60153800A	REEL OPEN 60B W/O 3/8” MAX 15M OIL (\$)		3/8”	60	-	3/8” FEMALE	3/8” FEMALE	15	-
HN60201200A	REEL OPEN 60B W/O .” MAX 20M OIL (\$)		1/2”	60	-	1/2” MALE	1/2” MALE	20	-
<b>WITH HOSE</b>									
HA6010120B	REEL O 60B W/” 33FT/10MT OIL NPT/BSP		1/2”	60	10 @ 30 L/MIN*	1/2” MALE	1/2” MALE	-	10
HA6015120B	REEL O 60B W/” 50FT/15MT OIL NPT/BSP		1/2”	60	16 @ 30 L/MIN*	1/2” MALE	1/2” MALE	-	15
HA6020120B	REEL OPEN 60B W/” 65F/20M OIL NPT/BSP		1/2”	60	25 @ 30 L/MIN*	1/2” MALE	1/2” MALE	-	20
HA60153400A	REEL OPEN 60B W/” 15MT OIL (\$)		3/4”	60	4,5 @ 30 L/MIN*	1” MALE	3/4” MALE	-	15
HA60101000A	REEL OPEN 60B W/ 1” 10MT OIL		1”	60	2 @ 30 L/MIN*	1” MALE	1” MALE	-	10
HA60203400A	REEL OPEN60B .” 20MT OIL IN/HOSE 1M(\$)		3/4”	60	-	3/4” FEMALE	3/4” FEMALE	-	20

(\*) PRESSURE DROP FOR OIL 200 CST

## OIL HOSE REEL