



KITS



PUMPS



METERS



METERED NOZZLES



NOZZLES



WASTE OIL  
EQUIPMENTS

# VACUBOX

## FEATURES

- AUTOMATIC OPERATION
- COMPRESSED AIR NOT REQUIRED
- NO EMPTYING NEEDED
- IDEAL FOR CENTRALIZED SYSTEMS
- ACOUSTIC SIGNAL
- VACUUM INDICATOR
- OPERATOR NOT REQUIRED
- ASPIRATION FROM DEEPSTICK BONNET
- HIGH SUCTION CAPACITY

The PIUSI VACUBOX is the perfect solution to automatically drain oil from a tank without the need of compressed air. Inside this all inclusive item there is an electric gear pump, a pressure switch and an electronic board that automatically switches off the pump once the tank is empty.

### PERFORMANCE

UP TO

**10 L/MIN**

TANK CAPACITY

**AC  
VOLTAGE**

POWER

BELOW

**65DB**

NOISE LEVEL\*



VACUBOX

### PACKAGING

CODE	WEIGHT		PACKAGING			
	KG	LBS	MM	INCH	PCS/PALLET	PCS/BOX
FO0500B00	10	22	295X295X325	11,6X11,6X12,8		1



FILTRATION



FLUID MONITORING



TANK MONITORING



HOSE REELS



ACCESSORIES



MERCHANDISE



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

## FUNCTIONING

### FULLY AUTOMATIC!



Suction directly from car and directly driven into waste oil storage tank.



## IN THE BOX

- VACUBOX
- INSTRUCTION MANUAL

## DETAILS



COMPACT DESIGN




AUTOMATIC STOPS


## DIMENSIONS

### VACUBOX FRONT

266




### VACUBOX SIDE "A"



246

### VACUBOX SIDE "B"



236

Dimensions expressed in millimeters

## MATERIALS

- PUMP BODY: CAST IRON
- PUMP GEARS: BRONZE
- SHAFT: STEEL

## TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			INLET
			L/MIN	GPM	AC V/HZ DC VOLT	POWER WATT	AMP. MAX.	BSP
FO0500B00	VACUBOX		1-10	0,25 - 2,5	230/50	350	2	1/2"

AVAILABLE AT 110-120 V / 60 HZ